

# Maxim Advanced for Wool

A 21st century protector designed for the unique properties of wool.

Contents: One U.S. Gallon (3.79 Litres)



- Oriental Rugs
- **Residential Wool Carpet**
- Commercial Wool Carpet

# 5.2 RTU pH

X = Primary Use ✓ = Secondary Use

- Excellent penetration on freshly cleaned rugs.
- Fluorochemical & Stain Resist Technology designed specifically for the special properties in wool, including the large number of dye sites.
- Covers up to 1200 sq. ft. per concentrated gallon, depending upon the thickness of the rug and the presence of prior protection.
- Freeze-thaw stable

## **DIRECTIONS:**

# **Pre-Cleaning Procedures**

- 1. Read entire label before using. Use only as directed.
- 2. Carefully pre-inspect the rug, fabric, or carpet before proceeding. Identify fiber content, construction, dye stability, shrinkage considerations and pre-existing damage. Always test every rug for dye bleeding potential. Carefully look for conditions which could contribute to cleaning related challenges such as pre-existing pet urine, water damage, fiber deterioration, past cleaning residues, and fringe discoloration. For rugs with whiter wool or white cotton fringes, pretest Maxim Advanced for Wool on back of rug to determine if protector dulls the white to any degree before proceeding. For silk rugs use either our Maxim Fine Fabric or Maxim Advanced for Upholstery with Dve Loc.

## **Protector Application**

- Dilution: Dilute by mixing 1 part concentrate protector with 2 parts water.
- Application: Apply to freshly cleaned Oriental rugs or wool carpet using an electric or battery powered sprayer maintaining 35 to 50 psi with an 8004 or 8005 TeeJet nozzle. Apply evenly over entire surface. Brush or rake to evenly distribute the protector.
- Coverage: 200 to 400\* sq ft per diluted gallon for freshly cleaned rugs or carpet. Coverage depends on carpet pile density; i.e. heavy pile requires 1 RTU gallon per 200 sq ft , flat woven rugs requires 1 RTU gallon per 400 sq ft for each side. For a rug with no prior protection consider doubling the application to assure the greatest level of protection.
- If accidental freezing occurs, allow to thaw at room temperature, then shake vigorously.

## **CONTENTS:**

Water (CAS # 7732-18-5), Acrylic Copolymer, Partially Fluorinated C6 Urethane Polymer, Phenolic Resin Condensate.

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to www.bridgepoint.com/sds for additional safety, regulatory and liability information.

MAXIM ADVANCED FOR WOOL (T)

May cause skin and eve irritation. Avoid contact

flush with plenty of water, seek medical advice if

irritation persists.

with skin and eves. In case of contact, immediately

Susceptible d'irriter la peau et les veux. Évitez tout

lavez-vous immédiament à la grande eau. Consultez

SEE SAFETY DATA SHEET

VOIR LA FICHE SIGNATÉTIQUE

contact avec la peau et les veux. S'il v a contact,

# Keep out of reach of children



## **HAZARD STATEMENTS:**

Causes eve irritation.

### PRECAUTIONARY STATEMENTS:

IF IN EYES: Rinse cautiously with water for several minutes. Remove Contact Lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF SKIN irritation occurs: Get medical advice/ attention.



Mantener fuera del alcance de los niños.

## INDICACIONES DE PELIGRO: Causa irritación al oio.

# **DECLARACIONES DE PRECAUCIÓN:**

Si en los oios: Eniuagarse cuidadosamente con agua por varios minutos. Remueva lentes de contacto si los está usando. Continúe eniugándose. Si en la piel: Lavarse con amplio jabón y agua. Si irritación a la piel ocurre: Obtenga consejo/ atención médica.



un médicin si l'irritation se fait persistante.

Another fine product from Bridgepoint Systems 4282 South 590 West, Salt Lake City, UT 84123 www.bridgepoint.com



